

2.563 kg

**SOEHNLE**

**PROFESSIONAL**



## Compact Scales 7745

The versatile scale where a stamped scale is required

Weighing ranges 6-40 kg

EU stamped, Class III

fast, compact, mobile

**Leaders in Weighing Technology**  
Industrial scales by Soehnle



# Compact Scales 7745

For special requirements at accuracy and stability in the hard daily employment

**The versatile scale where a stamped scale is required in industry and trade**

## Specification

- Mains operation: 220-235 V/50-60 Hz
- Accu/battery operation: 8 C-type batteries or NiCad batteries of the same size for permanent operation of approx. 8 hours. The backlit display is automatically switched off.
- Data interface RS232 (V24)
- Taring: Subtractive taring up to 100 % of the weighing range.
- Easy-care plastic housing. Platform made of chromenickel-steel, suitable for the food industry.

- Dimensions: 330 x 345 x 110 mm
- Weight: 6,9 kg.

## Design

- Officially stamped: approved throughout the European Union according verification class III (in kg or lb)
- Easy operation: Large-surface keys (pressure point membrane keyboard) for on/off/zero, tare, clear tare and data transmission to printer or computer.
- Easy reading: with 20 mm large, high-contrast backlit LCD.

- Reliable construction: Durable industrial quality for all applications in dry range.
- Dual range scale: The first part of the weighing range has a finer graduation. Thus the scale is more accurate.

## Included

- power supply with 2m cable.



Order No.	Finish	Platform size mm	Weighing range kg	Increments
7745.06.001	stamped	310 x 275	6	0 - 3 kg = 1g 3 - 6 kg = 2g
7745.08.001	stamped on site	310 x 275	8	0 - 4 kg = 1g 4 - 8 kg = 2g
7745.15.001	stamped	310 x 275	15	0 - 6 kg = 2g 6 - 15 kg = 5g
7745.20.001	stamped on site	310 x 275	20	0 - 8 kg = 2g 8 - 20 kg = 5g
7745.30.001	stamped	310 x 275	30	0 - 15 kg = 5g 15- 30 kg = 10g
7745.40.001	stamped on site	310 x 275	40	0 - 20 kg = 5g 20- 40 kg = 10g
7745.40.002	stamped	310 x 275	40	0 - 20 kg = 5g 20- 40 kg = 10g



Uw SOEHNLE  
leverancier:

Weegtechniek Holland B.V.

Patroonsweg 23 - 27  
3892 DA Zeewolde

Tel. 036 522 20 30  
Fax. 036 522 20 60  
Email info@soehnle.nl  
Site www.soehnle.nl

**SOEHNLE**  
PROFESSIONAL

[www.soehnle.nl](http://www.soehnle.nl)  
[info@soehnle.nl](mailto:info@soehnle.nl)